N THE UNITED STATES PATENT AND TRADEMARK OFFICE

CAT & TO LOCATE
Application Serial No
Filing Date February 24, 2000
Inventor David R. Hembree
Assignee
Group Art Unit
Examiner V. Nguyen
Attorney's Docket No
Confirmation No
Client No
Title: Wafer Processing Apparatuses and Electronic Device Workpiece Processing
Apparatuses (As Amended)

RESPONSE TO FEBRUARY 17, 2004 OFFICE ACTION

RECEIVED

JUN 28 2004
TECH CENTER 2800

To:

Mail Stop Amendment

Assistant Commissioner for Patents

P.O. Box 1450

Alexandria VA 22313-1450

From:

James D. Shaurette (Tel. 509-624-4276; Fax 509-838-3424)

Wells, St. John, P.S.

601 W. First Avenue, Suite 1300 Spokane, WA 99201-3828

Sir:

Responsive to the Office Action dated February 17, 2004, Applicant amends and remarks as follows:

AMENDMENTS

06/24/2004 HVUONG1: 00000006: 09512968

03 FC:1202

162.00 0

In the Claims

Claims 1-63 are canceled.

64. [Previously Presented] A wafer processing apparatus comprising:

a wafer holder adapted to receive a wafer having an electrical coupling, the wafer holder including an electrical coupling configured to electrically couple with the electrical coupling of the wafer and communicate signals between the wafer and the wafer holder of the wafer processing apparatus for fabrication of integrated circuitry using the wafer processing apparatus.

- 65. [Previously Presented] The wafer processing apparatus according to claim 64 further comprising a data gathering device coupled with the electrical coupling of the wafer holder and configured to receive the signals.
- 66. [Previously Presented] The wafer processing apparatus according to claim 65 further comprising a contact plate configured to communicate the signal intermediate the wafer holder and the data gathering device.
- 67. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder includes a first surface, a second surface, and an electrical interconnect configured to electrically couple the first surface and the second surface.

- 68. [Previously Presented] The wafer processing apparatus according to claim 67 wherein the first surface of the wafer holder is configured to face a received wafer and the second surface is configured to face a chuck.
- 69. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder includes a plurality of electrical couplings adapted to couple with a plurality of electrical couplings of the wafer.
- 70. [Previously Presented] The wafer processing apparatus according to claim64 wherein the wafer holder comprises a chuck.
- 71. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder comprises a chuck configured to receive one of a calibration wafer and a production wafer.
- 72. [Previously Presented] The wafer processing apparatus according to claim 71 wherein the wafer holder includes vacuum chambers adapted to receive a vacuum to couple one of the calibration wafer and the production wafer with the chuck.
- 73. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder comprises an intermediate member adapted to couple with a chuck.

- 74. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder includes a vacuum chamber adapted to receive a vacuum to couple a received wafer with the wafer holder
- 75. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the electrical coupling of the wafer holder comprises a conductive column configured to extend outward from plural surfaces of the wafer holder.
- 76. [Previously Presented] The wafer processing apparatus according to claim 75 further comprising a contact plate including circuitry configured to provide electrical connection with the conductive column.
- 77. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the electrical coupling of the wafer holder is adapted to contact the electrical coupling of the wafer.
- 78. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder is adapted to expose the wafer to a processing environment to process the wafer.

79. [Previously Presented] A wafer processing apparatus comprising:

a wafer holder having circuitry configured to communicate a process signal from a received wafer and the process signal containing information regarding processing of the wafer using the wafer processing apparatus.

- 80. [Previously Presented] The wafer processing apparatus according to claim
 79 wherein the wafer holder is adapted to expose the wafer to a processing environment to process the wafer.
 - 81. [Previously Presented] A wafer processing apparatus comprising:

a chuck including a surface, an electrical coupling adjacent the surface, and \underline{an} electrical interconnect configured to connect with the electrical coupling of the chuck and conduct a signal within the chuck;

an intermediate member adapted to receive a wafer and the intermediate member having a first surface and a second surface and the intermediate member including:

an electrical coupling adjacent the second surface; and

an electrical interconnect configured to connect the electrical coupling adjacent the first surface and the electrical coupling adjacent the second surface; and

a wafer configured to couple with the second surface of the intermediate member, the wafer including a sensor and an electrical coupling configured to provide electrical

connection of the sensor with the electrical coupling of the second surface of the intermediate member.

- 82. [Previously Presented] The wafer processing apparatus according to claim81 further comprising a data gathering device coupled with the electrical coupling of the chuck and configured to receive the signal.
- 83. [Previously Presented] The wafer processing apparatus according to claim 82 further comprising a contact plate configured to communicate the signal intermediate the chuck and the data gathering device.
- 84. [Previously Presented] The wafer processing apparatus according to claim81 wherein the sensor comprises a resistance temperature device.
- 85. [Previously Presented] The wafer processing apparatus according to claim81 wherein the wafer comprises a calibration wafer.
- 86. [Previously Presented] The wafer processing apparatus according to claim 81 wherein the electrical interconnect comprises a conductive column configured to extend outward from plural surfaces of the chuck.

- 87. [Previously Presented] The wafer processing apparatus according to claim 86 further comprising a contact plate including circuitry configured to provide electrical connection with electrical couplings of the chuck.
- 88. [Previously Presented] The wafer processing apparatus according to claim 81 wherein the intermediate member is configured to expose the wafer to a processing environment to process the wafer.
 - 89. [Previously Presented] A wafer processing apparatus comprising:

a chuck including a surface, a plurality of electrical couplings adjacent the surface, and a plurality of electrical interconnects configured to connect with respective electrical couplings of the chuck and conduct signals within the chuck;

an intermediate member adapted to receive a wafer and the intermediate member having a first surface and a second surface and the intermediate member including:

a plurality of electrical couplings adjacent the first surface and configured to couple with respective electrical couplings of the chuck:

a plurality of electrical couplings adjacent the second surface; and

a plurality of electrical interconnects configured to electrically connect the electrical couplings of the first surface with respective electrical couplings of the second surface:

a calibration wafer configured to couple with the second surface of the intermediate member, the calibration wafer including a plurality of resistance temperature devices configured to generate process signals, and a plurality of electrical connections configured

to electrically connect the resistance temperature devices with respective electrical couplings of the second surface of the intermediate member; and

a data gathering device coupled with the electrical interconnects of the chuck and configured to receive the process signals from the resistance temperature devices through the intermediate member and the chuck.

- 90. [Previously Presented] The wafer processing apparatus according to claim 89 wherein the intermediate member is configured to expose the wafer to a processing environment to process the wafer.
- 91. [Currently Amended] An electronic device workpiece processing apparatus comprising:

a workpiece holder adapted to receive an electronic device workpiece having an electrical coupling, the workpiece holder including an electrical coupling configured to electrically couple with the electrical coupling of the electronic device workpiece and communicate signals between the electronic device workpiece and the workpiece holder during fabrication of integrated circuitry of the electronic device workpiece using the electronic device workpiece processing apparatus, wherein the workpiece holder includes a vacuum chamber adapted to receive a vacuum to couple a received electronic device workpiece with the workpiece holder.

- 92. [Previously Presented] The apparatus of claim 91 wherein the workpiece holder is configured to expose the electronic device workpiece to a processing environment to process the electronic device workpiece.
- 93. [Previously Presented] An electronic device workpiece processing apparatus comprising:

a workpiece holder adapted to receive an electronic device workpiece having an electrical coupling, the workpiece holder including an electrical coupling configured to electrically couple with the electrical coupling of the electronic device workpiece and communicate signals between the electronic device workpiece and the workpiece holder, wherein the electrical coupling of the workpiece holder is configured to extend outward from plural surfaces of the workpiece holder; and

a contact plate including circuitry configured to provide electrical connection with the conductive column.

94. [Previously Presented] The apparatus of claim 93 wherein the workpiece holder is configured to expose the electronic device workpiece to a processing environment to process the electronic device workpiece.

95. [Previously Presented] An electronic device workpiece processing apparatus comprising:

a chuck including a surface, an electrical coupling adjacent the surface, and electrical interconnect configured to connect with the electrical coupling of the chuck and conduct a signal within the chuck;

an intermediate member having a first surface and a second surface and the intermediate member including:

an electrical coupling adjacent the first surface and configured to couple with the electrical coupling of the chuck;

an electrical coupling adjacent the second surface; and

an electrical interconnect configured to connect the electrical coupling adjacent the first surface and the electrical coupling adjacent the second surface;

an electronic device workpiece configured to couple with the second surface of the intermediate member, the electronic device workpiece including a sensor and an electrical coupling configured to provide electrical connection of the sensor with the electrical coupling of the second surface of the intermediate member:

a data gathering device coupled with the electrical coupling of the chuck and configured to receive the signal; and

a contact plate configured to communicate the signal intermediate the chuck and the data gathering device.

- 96. [Previously Presented] The apparatus of claim 95 wherein the intermediate member is configured to expose the electronic device workpiece to a processing environment to process the electronic device workpiece.
- 97. [Previously Presented] An electronic device workpiece processing apparatus comprising:

a chuck including a surface, an electrical coupling adjacent the surface, and electrical interconnect configured to connect with the electrical coupling of the chuck and conduct a signal within the chuck;

an intermediate member having a first surface and a second surface and the intermediate member including:

an electrical coupling adjacent the first surface and configured to couple with the electrical coupling of the chuck;

an electrical coupling adjacent the second surface; and

an electrical interconnect configured to connect the electrical coupling adjacent the first surface and the electrical coupling adjacent the second surface; and

an electronic device workpiece configured to couple with the second surface of the intermediate member, the electronic device workpiece including a sensor comprising a resistance temperature device, and an electrical coupling configured to provide electrical connection of the sensor with the electrical coupling of the second surface of the intermediate member.

- 98. [Previously Presented] The apparatus of claim 97 wherein the intermediate member is configured to expose the electronic device workpiece to a processing environment to process the electronic device workpiece.
- 99. [Previously Presented] An electronic device workpiece processing apparatus comprising:

a chuck including a surface, an electrical coupling adjacent the surface, and electrical interconnect configured to connect with the electrical coupling of the chuck and conduct a signal within the chuck;

a contact plate including circuitry configured to provide electrical connection with the electrical coupling of the chuck;

an intermediate member having a first surface and a second surface and the intermediate member including:

an electrical coupling adjacent the first surface and configured to couple with the electrical coupling of the chuck;

an electrical coupling adjacent the second surface; and

an electrical interconnect configured to connect the electrical coupling adjacent the first surface and the electrical coupling adjacent the second surface, wherein the electrical interconnect comprises a conductive column configured to extend outward from plural surfaces of the chuck; and

an electronic device workpiece configured to couple with the second surface of the intermediate member, the electronic device workpiece including a sensor and an electrical

coupling configured to provide electrical connection of the sensor with the electrical coupling of the second surface of the intermediate member.

- 100. [Previously Presented] The apparatus of claim 99 wherein the intermediate member is adapted to expose the electronic device workpiece to a processing environment to process the electronic device workpiece.
- 101. [Previously Presented] An electronic device workpiece processing apparatus comprising:

an electronic device workpiece including a sensor and an electrical coupling; and an intermediate member including a surface having an electrical coupling and adapted to expose the electronic device workpiece to a processing environment to process the electronic device workpiece;

wherein the electrical coupling of the electronic device workpiece is configured to provide electrical connection of the sensor with the electrical coupling of the surface of the intermediate member.

- 102. [Previously Presented] The apparatus according to claim 101 wherein the electronic device workpiece comprises a wafer.
- 103. [Previously Presented] The wafer processing apparatus according to claim64 wherein the wafer holder is configured to support a wafer for processing within the wafer

processing apparatus to form a plurality of discrete integrated circuits of a plurality of respective dies to be singulated from the wafer at a subsequent moment in time.

- 104. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer holder is configured to expose a wafer to a processing environment within the wafer processing apparatus to form a plurality of discrete integrated circuits of a plurality of respective dies to be singulated from the wafer at a subsequent moment in time.
- 105. [Previously Presented] The wafer processing apparatus according to claim 64 further comprising a processing area of the wafer processing apparatus configured to process a wafer supported using the wafer holder to fabricate a plurality of discrete integrated circuits of a plurality of respective dies to be singulated from the wafer at a subsequent moment in time.
- 106. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer processing apparatus is configured to process a wafer supported using the wafer holder to fabricate a plurality of discrete integrated circuits of a plurality of respective dies to be singulated from the wafer at a subsequent moment in time.
- 107. [Previously Presented] The wafer processing apparatus according to claim 64 wherein the wafer comprises a semiconductive wafer comprising a plurality of integrated circuit dies prior to singulation of at least one of the dies at a subsequent moment in time.

108. [Previously Presented] An article of manufacture comprising:

a wafer processing apparatus configured to fabricate integrated circuitry using a plurality of wafers and comprising a wafer holder configured to receive at least one of the wafers having an electrical coupling, and wherein the wafer holder comprises an electrical coupling configured to electrically couple with the electrical coupling of the at least one wafer and to communicate signals between the at least one wafer and the wafer holder.

- 109. [Previously Presented] The article of claim 108 wherein the electrical coupling of the wafer holder is configured to contact the electrical coupling of the wafer.
- 110. [Previously Presented] The article of claim 108 wherein the communicated signals comprise information regarding processing of the wafer using the wafer processing apparatus.
- 111. [Previously Presented] An electronic device workpiece processing apparatus comprising:

an intermediate member comprising a first surface and a second surface, wherein the second surface comprises an electrical coupling; and

an electronic device workpiece including a sensor and an electrical coupling configured to provide electrical connection of the sensor with the electrical coupling of the second surface of the intermediate member.

- 112. [New] The wafer processing apparatus according to claim 64 wherein the electrical coupling of the wafer holder is electrically conductive to establish an electrical connection with the electrical coupling of the wafer wherein electrons of the signals are exchanged between the electrical couplings of the wafer holder and the wafer.
- 113. [New] The wafer processing apparatus according to claim 64 wherein the signals are generated using electrical circuitry of the wafer.
- 114. [New] The wafer processing apparatus according to claim 64 wherein the signals comprise electrical signals.
- 115. [New] The wafer processing apparatus according to claim 79 wherein the process signal comprises information regarding the processing of the wafer for fabrication of integrated circuitry using the wafer processing apparatus.
- 116. [New] The wafer processing apparatus according to claim 79 wherein the wafer holder is configured to receive the process signal comprising an electrical signal using an electrical coupling of the wafer holder in electrical contact with an electrical coupling of the wafer.
- 117. [New] The electronic device workpiece processing apparatus according to claim 91 wherein the communicated signals comprise information regarding processing of the wafer for fabrication of the integrated circuitry using the wafer processing apparatus.

- 118. [New] The electronic device workpiece processing apparatus according to claim 91 wherein the communicated signals comprise electrical signals.
- 119. [New] The article according to claim 108 wherein the communicated signals comprise information regarding processing of the wafers for fabrication of the integrated circuitry using the wafer processing apparatus.
- 120. [New] The article according to claim 108 wherein the electrically coupled electrical couplings of the wafer and the wafer holder are in electrical contact with one another to communicate the signals comprising electrical signals between the at least one wafer and the wafer holder.

E	· ×	00-00	<i>-</i> /	α
7004 June 1 the Paperwork	Reduction Act of 1995, no oen	U.S. P	Approved for use through alent and Trademark Office; U.S. DE cotion of information unless it displays 05/512,968	PTO/SB/21 (02-04) 1 07/31/2006, OMB 0551-0031 PARTMENT OF COMMERCE 5 a valid OMB control number
, TRAN	SMITTAL	Filing Date	2/24/2000	REC "
F	ORM	First Named Inventor	David R. Hembree	
(to be used for all corre	spondence after initial filing)	Art Unit	2829	JUN 28 2014
		Examiner Name	V. Nguyen	2020
Total Number of Pages	in This Submission	Attorney Docket Number	MI22-1363	TECH CENTER 280
	FN	CLOSURES (Check all	that anniv)	
Extension of Tim Express Abando X Information Disc Certified Copy or Document(s) Response to Mis Incomplete Apil	ched	Form PTO-	ot Technolog Appeal Com of Appeals an Appeal Com of Appeals an Appeal Netic Proprietary in Other Enclos Identify below Recture Receigt Pos As 452,00ches	sure(s) (please w):
Firm Jame:	SIGNATURE s.D. Shaurette, Reg. No. 35 St. John, P.S.	OF APPLICANT, ATTO	*	
I hereby certify that this sufficient postage as the date shown below.	correspondence is being fa	csimile transmitted to the USPTO	O or deposited with the United St. Patents, P.O. Box 1450, Alexand	ates Postal Service with dria, VA 22313-1450 on
Signature	Dinity	Corton	Date	4/7/04

This collection of information is required by 37 CFR 1. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentially is governed by 35 U.S.C. 122 and 37 CFR 1.1.4. This collection is estimated to 2 hours to complete, including althering, presanding, and submitting the completed application from to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office. U.S. Department of Commerce, P.O. Box 1450, Alexandria, V.A. 2313-1450.

ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, V.A. 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

1003 530

Signature

2003 265

Plant filing fee

Approved for use through 07/31/2008 OMB 085-

Under Paperwork Reduction Act of 1995, no persons are requ	ired to	respond	to a co	Patent	and Ir of info	ademark Office; U.S. DEPARTMENT (OF COMMERCE			
FÉETRANSMITTA	ı					ompl te if Known	control number.			
ILLIKANSIVIIIIA	L	Appl	Application Number			09/512,968				
for FY 2004		Filing Date				2/24/2000	RECE	VED		
Effective 10/01/2003. Patent fees are subject to annual revision	,	First	Name	d Inve	ntor	David R. Hembree				
Applicant claims small entity status. See 37 CFR 1.27		Examiner Name VNguyen					JUN 28	Zuu4		
		Art U	Init							
TOTAL AMOUNT OF PAYMENT (\$) 452.00		Attorney Docket No. MI 22-1363					TECH CENT	D 2000		
METHOD OF PAYMENT (check all that apply)	Г	FEE CALCULATION (continued)								
Check	Fee Code 1051 1052 1053 1812 1804 1805	130 50 130 2,520 920* 1,840*	Fee Code 2051 2052 1053 1812 1804 1805	Fee (\$) 65 25 130 2.520 920	Surch Surch cover Non-E For fili Reque Exam	Fee Description arge - late filing fee or oath arge - late filing fee or sheet ingids specification ng a request for ex parte reexaminatio sating publication of SIR prior to mer action setting guidecation of SIR after mer action				
FEE CALCULATION	1251	110	2251	55	Exten	sion for reply within first month	110.00			
BASIC FILING FEE	1252		2252	210	Exter	sion for reply within second month				
rge Entity Small Entity	1253		2253	475	Exter	sion for reply within third month				
ee Fee Fee Fee Fee Description Fee Paid ode (\$) Code (\$)	1254	1,480	2254	740	Exten	sion for reply within fourth month				
001 770 2001 385 Utility filing fee	1255	2,010	2255	1,005	Exten	sion for reply within fifth month				
202 340 2002 170 Design filing fee	1401	330	2401	165	Notice	of Appeal				

1402 330 2402 , 165 Filing a brief in support of an appeal

	1-00-		rveisade ming ice	1400	230	2703	143	ricquest for oral fleating		
1005 160	2005	80	Provisional filing fee	1451	1,510	1451	1,510	Petition to institute a public use proceeding		
	l	s	UBTOTAL (1) (\$) - 0 -	1452	110	2452	'55	Petition to revive - unavoidable		
2 FYTRA	CL AIM		FOR UTILITY AND REISSUE	1453	1,330	2453	665	Petition to revive - unintentional		
	CLAIII	LLC	Fee from	1501	1,330	2501	655	Utility issue fee (or reissue)		
Total Claims	E 7		Extra Claims below Fee Paid		480	2502	240	Design issue fee		
Independent		J-4 [*] 8		1503	640	2503	320	Plant issue fee		
Claims Multiple Depe		-12	= _ 0 × = _ 0.00	1460	130	1460	130	Petitions to the Commissioner		
			L	1807	50	1807	50,	Processing fee under 37 CFR 1.17(q)		
Large Entity Fee Fee	Small		Fee Description.	1806	180	1806	180	Submission of Information Disclosure Stmt	180.00	
Code (\$)	Code			8021	40	8021	40	Recording each patent assignment per	* *	
1202 18	220	2 9	Claims in excess of 20					property (times-number of properties)		
1201 86	220	1 43	Independent claims in excess of 3	1809	770	2809	385	Filing a submission after final rejection (37 CFR 1.129(a))		
1203 290	220	3 145	Multiple dependent claim, if not paid	1810	770	2810.	385	For each additional invention to be		
1204 86	220	4 43	** Reissue independent claims					examined (37 CFR 1.129(b))		
			over original patent	1801	770	2801	385	Request for Continued Examination (RCE)		
1205 18	220	5 9	** Reissue claims in excess of 20 and over original patent	1802	900	1802	900			
						1.5		of a design application		
		SUB	TOTAL(2) (\$) 162.00		Other fee (specify)					
**or number previously paid, if greater, For Relassues, see above Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$) 290.00									.00	
SUBMITTED BY (Complete (# applicable))										
Name (PrinVType) James D. Shaurette A						ion No.•	20	.833 Telephone (509) 62	1 11276	
			St. St. Gall Cliff		ttornev/.	igent)	JJ,	.033 1 (509,) 612	+-44/b	

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This callection of information is required by 37 CFR 1.17 and 1.27. The information and authorization on P IU-2/us.

This callection of information is required by 37 CFR 1.17 and 1.27. The information is required to totain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 38 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gehtering, preparing, and submitting the completed application from to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form andord suggestions for reducing his burdens, should be sent to the Chef Information Officer, U.S. Petart and Tademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS.
SRMDT TO: Commissioner for Patient & P.D. Dev 1450, Alexandria, VA 22313-1450. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

(Attorney/Agent)

6/17/04

PTO/SB/17 (10-03)
Approved for use through 07/31/2006, OMB 0651-0032
J.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Once are Paper	fronk Reduction 200 of 199	5 no cersons are rect	ired to	rescond	to a co	lection	of informatio	n unless it displ	avs a valid OMP	COMMER
FFF	TRANS	ATTIME	1				Compl	te if Know	7	santroi num
'	· ILWINS	DIVILLI I A	L	Appl	lication	Numi	ber 09	/512,968	1 DE	0=0
	for FY 2	000 <i>4</i>		Filing	g Date		2/:	24/2010	<u>g ni</u>	<u> </u>
Effective 100	1/2003, Patent fees are su			First	Name	d Inve	ntor Da	MICHO!	embree	
			n.		niner N		.141.	77	cilbi ce	JUN 28 2 (
Applicant clai	ms small entity status.	See 37 CFR 1.27		Art L			28	Nguyen		
TOTAL AMOUN	T OF PAYMENT	(\$) 452.00		_	nev Do	ckat !		22-1363	TECH	CENTER
METHOD C	F PAYMENT (check		Τ					ATION (co		
	edit card Money [Other None	3 4	DDIT	IONA			LATION (co	ntinued)	
X Deposit Accour	Order L			Entity						
Deposit			Fee	Fee	Fee	Fee	Fe	e Descriptio	n	
Account 23 Number	-0925	1	1051		Code 2051					Fee Paid
Deposit			1052		2052			late filing fee or late provisional		<u> </u>
Name	ls St. John, F		1				cover sheet		ming ree or	—
he Director is autho	rized to: (check all that ap		1053	130 2,520	1053		Non-English			-
Charge fee(s) indic		lit any overpayments	1804	920*					rte reexaminatio	^
Charge any addition	anal fee(s) or any underpay cated below, except for the	ment of fee(s)			1804		Examiner act			
the above-identified	deposit account.	e ming ree	1805	1,840*	1805	1.840*	Requesting p Examiner ac	publication of Sition	IR after	L
	EE CALCULATION		1251	110	2251	55	Extension fo	r reply within fir	st month	110.0
BASIC FILING	FEE		1252	420	2252	210	Extension fo	r reply within se	cond month	
ege Entity Small E			1253	950	2253	475	Extension fo	r reply within th	ird month	
ode (\$) Code (s) Fee Description	Fee Paid	1254	1,480	2254	740	Extension fo	r reply within fo	urth month	L
001 770 2001 :	385 Utility filing fee		1255	2,010	2255			r reply within fif		
002 340 2002	170 Design filing fee		1401	330	2401	165	Notice of Apr	peal		
	265 Plant filing fee		1402	330	2402	165	Filing a brief	in support of ar	appeal	
	385 Reissue filing fee		1403	290	2403	145	Request for o	oral hearing		
005 160 2005	80 Provisional filing	fee	1451	1,510	1451	1,510	Petition to ins	stitute a public u	se proceeding	
	SUBTOTAL (1)	(\$) - 0 -	1452	110	2452	55	Petition to rev	vive - unavoidal	ole	
EXTRA CLAIM	FEES FOR UTILITY	AND DEICCUE	1453	1,330	2453	665	Petition to re-	vive - unintentio	nal	L
	F	ee from	1501		2501	655	Utility issue for	ee (or reissue)		
otal Claims 57		8.00 = 162.00	1502	480	2502	240	Design issue	fee		
dependent 12	-12·= 0 x	= 0.00	1503	640	2503	320	Plant issue fe	ee		
fultiple Dependent			1460	130	1460	130	Petitions to the	he Commission	er	
arge Entity Small	Entity		1807	50	1807	50	Processing fe	e under 37 CF	R 1.17(q)	
ee Fee Fee	Fee Fee Descripti	<u>on</u>	1806	180	1806			f Information Di		180.00
Code (\$) Code 202 18 220			8021	40	8021	40	Recording ear	ch patent assign s number of pr	nment per	
			1809	770	2809	385	Filing a subm	ission after fina		
201 86 220 203 290 220		ms in excess of 3					(37 ČFR 1.12	(9(a))	•	ļ
204 86 220		ent claim, if not paid	1810	770	281	385	For each addi	itional invention CFR 1.129(b))	to be	
220	over original pa	atent	1801	770	<i>M</i>	.) 85		Continued Exan		
1205 18 220	5 9 ** Reissue claims and over origin	s in excess of 20	1802	. % [No.	900	Request for	expedited exam		
	-	·	Other?		cify)		of a design a	pplication		
**or number previous	SUBTOTAL (2) sly paid, if greater: For Rei.			by E		ing Fe	e Paid	SUBTOTAL	(3) (\$) 290	- 00
UBMITTED BY		7	₩		_	_				.00
ame (Print/Type)	James D. Sha	urette_A		gistratio		20		(Complete (if Telephone		
gnature	1 30. 3114	3 4	(A)	tomey/Ac	genti	39,	833		(509 ₁) 62	4-4276
y received G	11-11-							Date		

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This collection of information is required by 37 CPR. 17 and 12.7 The information and authorization on nTU-2045.

This collection of information is required by 37 CPR. 17 and 12.7 The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentially is governed by 35 U.S.C. 122 and 37 CPR. 1.14. This collection is estimated to take 12 minutes to complete, including pathening, preparing, and submitting the completed application from the USPTO. The will very operating goon the individual case. Any comments on the amount of time you require to complete his form and/or suggestions for reducing his burden, should be sent to the Chief Information Officer, U.S. Papent and Trademark Office, U.S. Department of Commerce, P.O. Des v1450, Alexandria, V.A 2213-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, V.A 2213-1450.